

Codification of Spare Sleeves type RM

for Manual and Control Pinch Valves of RV Series



Example Code-No.:

RM	100	1	10	1	1	C
1	2	3	4	5	6	7

1. Description: **RM** – Sleeves for manual and control pinch valves of RV series
- RMA** – Sleeves for air operated pinch valves of RVA series
2. Diameter: in mm
3. Sleeve:
- | | |
|---|--|
| 1 – NR (natural rubber) | 5 – CR (neoprene) |
| 1LS – NR food black | 5W – CR white |
| 2 – EPDM (Ethylen-Propylen-Dien) | 6 – NBR (nitrile) |
| 2LS – EPDM food black | 6/3L – NBR/SBR food |
| 2LW – EPDM food white | 6W – NBR food white |
| 2H – EPDM high temperature, 115°C | 7 – CSM (hypalone) |
| 2HT – EPDM high temperature, 130°C | 8 – IIR (butyle) |
| 2PU – EPDM, polyurethane coated | 9 – PU (polyurethane) |
| 3 – SBR (styrene butadiene rubber) | PGR – PGR (natural rubber)
anti-abrasive |
| 4 – FPM (fluorine rubber [viton]) | |
4. Pressure stage:
- | | | |
|------------------|------------------|-------------------------|
| 1 – 1 bar | 6 – 6 bar | 10 – 10 bar etc. |
|------------------|------------------|-------------------------|
5. Flange drilling:
- | | | |
|----------------------|---------------------|------------------------------|
| 1 – DIN PN 10 | 4 – DN PN 40 | 7 – ANSI 600 |
| 2 – DIN PN 16 | 5 – ANSI 150 | 8 – ANSI 900 |
| 3 – DIN PN 25 | 6 – ANSI 300 | 9 – other, e.g. ON 64 |
6. Construction length:
- | | | |
|--------------------------|-----------------------------|---------------------------|
| 1 – DIN 3202 F5 | 2 – DIN 3202 F15 | 3 – ASME B16–short |
| 4 – ASME B16–long | 5 – ISO 5752, Tab. 6 | |
7. Accessories:
- | | |
|------------------------------------|---------------------------------|
| C – electrical control wire | Z – smooth inner surface |
| T – opening tabs | X – acc. specification |
| L – limit switch | D – double cone |